NEW DAILY MINIBUS EE

BUSINESS

IVECO

DAILY





DAILY MINIBUS E6 SPECIFICATIONS

DIMENSIONS

	I	1	r	1
	11+1 Shuttle	16+1 Shuttle	16+1 Executive	22+1 Shuttle
Wheelbase	3520 mm (L)	4100 mm (L)	4100 mm (L)	4100 mm (L)
Overall Length	5950 mm	7515 mm	7515 mm	7515 mm
Width	2052 mm	2174 mm	2174 mm	2174 mm
Height	2784 mm (H2)	2905 mm (H2)	3090 mm (H3)	2905 mm (H2)
Standing Height	1820 mm	1820 mm	2010 mm	1820 mm
Front Overhang	1008 mm	1008 mm	1008 mm	1008 mm
Rear Overhang	1422 mm	2407 mm	2407 mm	2407 mm
Front Track	1724 mm	1725 mm	1725 mm	1725 mm
Rear Track	1540 mm	1661 mm	1661 mm	1661 mm
Turning Diameter: Wall-to-Wall	12744 mm	14758 mm	14758 mm	14758 mm
Turning Diameter: Kerb-to-Kerb	12084 mm	14108 mm	14108 mm	14108 mm
Approach/ Departure Angles	19.05°/22.61°	19.61°/21.62°	19.61°/21.62°	19.61°/21.62°
GVM	4495 kg	6100 kg	6100 kg	6100 kg
Towing Capacity with Braked Trailer	3500 kg	3500 kg	3500 kg	3500 kg
Max.Axle Load Front/Rear	2100/3100 kg	2200/4200 kg	2200/4200 kg	2200/4200 kg

L - Long H2/H3 - Reference to Interior Roof Height

ENGINE

Type: 180 hp IVECO FIC (EURO 6) 4 stroke diesel with direct-injection,

Variable Geometry Turbocharger (VGT) and intercooler

Maximum Output: 180 hp @ 2800 - 3500 rpm

Maximum Torque: 430 Nm @ 1500 - 3000 rpm Emissions Technology: Exhaust Gas Recirculation system + Selective Catalytic Reduction

Total Displacement: 3.0 litre

Exhaust: Horizontally positioned muffler on the right side and tailpipe

located mid-way down right side of vehicle.

TRANSMISSION

• 8-speed ZF Torque Converter Automatic (Hi-Matic with ECO mode) **Type:** 8V470A (180 hp)

Ist 4.696, 2nd 3.130, 3rd 2.104, 4th 1.667, 5th 1.285, 6th 1.000, 7th 0.839 OD, 8th 0.667 DOD, Rev. 3.297

STEERING

- Power steering
- 390mm diameter steering wheel with telescopic adjustment

FRONT AXLE & SUSPENSION

Axle: Independent wheels

Suspension: Independent with torsion bar

REAR AXLE & SUSPENSION Axle: Rigid, Twin wheel,

3520L: Ratio 3.308

4100L: Ratio 4.3

Suspension: Pneumatic Air Suspension with ECAS

BRAKES

Type: ABS + ESP

Front: Disc brakes **Rear:** Disc brakes

Parking Brake: Manual brake operating on rear axle Service Brakes: Dual circuit with vacuum servo

· Pad wear warning light for front and rear brakes

FUEL SYSTEM

Fuel Tank Capacity: 90L AdBlue Tank: 25L

CHASSIS

C Section steel longitudinal side members and tubular cross members

ELECTRICAL SYSTEM Battery: I2V - II0 Ah

Smart Alternator: 12V - 180 A


• Trailer wiring to rear of chassis

WHEELS & TYRES

Wheels: ||+| Seater: 5.5] × RI6 16+1 & 22+1 Seater: 6] x R16 Tyre Size: ||+| Seater: 195/75 RI6

16+1 & 22+1 Seater: 225/65 RI6





CABIN FEATURES

Driver

- **IVECONNECT** multimedia system
- Steering wheel audio/phone controls
- Bluetooth connectivity
- Anti-corrosion protection by full cataphoretic dipping
- Two rear doors 270° opening with heated windows
- Heated and electrically adjustable mirrors
- Electric bus plug door
- Athermic windscreen
- Single athermic glued windows
- Thermo-acoustic insulation
- 4 speed electrical fans with air distribution functions and air recirculation for driver
- A/C for driver with automatic control
- Passenger air conditioning through air channels on luggage rack
- Reverse camera
- PVC Floor covering. Premium timber looking PVC floor covering is standard Executive 16
- Side wall covering
- Windows frame covering in ABS plastics
 - Luggage racks on both sides. Executive 16 comes standard with individual LED lights
- Emergency and ventilation roof hatch
- Passenger seats covered in fabric. Leather seats standard in Executive 16
- 3 point seatbelts
- LED lights on entry steps
- Day time running lights
- Fog lights
- A/C casing same body colour
- Door fitted with glass defrosting and silicon gasket
- Independent passenger heating system Pleated curtains on passenger windows

DRIVER COMPARTMENT & DASHBOARD

- Adjustable and air suspended driver seat
- Electric driver window
- Dedicated storage compartments
- LDWS (Lane Departure Warning System)
- Driver's airbag
- Cruise control

SECURITY

- Central locking with remote control
- Steering lock
- Engine immobiliser



WWW.IAECOCOMAU THE INFORMATION IN THIS DOCUMENT WAS CORRECT AT THE TIME OF PRINTING ALL WEIGHTS - AVAILABILITY, WE RESERVE 9238 2200 INCLUDED IN THE STANDARD VEHICLE AND ARE SUBJECT 8 BOX 117 DANDENONG, VICTORIA 3175 TELEPHONE: EQUIPMENT NOT Ö. HWY, DANDENONG, VICTORIA 3175 DOD **PRINCES** HISH 261 065 .86 004 ONLY UMITED A.B.N. IVECO TRUCKS AUSTRALIA AND MEASUREI