Coolant



Highway Plus Coolant

Product summary & features	2
Product details	3-4
Technical specifications and information	5

Product summary



ENGINE COOLANT

Part numbers: ZFGCC36082HP (4I), ZFGCC36083HP (10I), ZFGCC36084HP (20I), ZFGCC36085HP (208I) and ZFGCC36086HP (1000I)

The new global benchmark in coolant technology!

- ✓ Extended life coolant with 500,000 kilometre or 6,000 hour service interval and 1.5 million Kilometre or 20,000 hour life with good maintenance
- ✓ Non-Nitrite formula that provides advanced liner pitting, scale and corrosion protection
- ✓ Provides freeze protection
- ✓ Compatible with ALL coolants
- ✓ Meets global OEM specifications for Nitrite, Amine, Phosphates and Silicate Free formula



Heavy Duty, Pre-mixed Coolant 4L ZFGCC36082HP



Heavy Duty, Pre-mixed Coolant 10L ZFGCC36083HP



Heavy Duty, Pre-mixed Coolant 20L ZFGCC36084HP





Heavy Duty, Pre-mixed Coolant 208L ZFGCC36085HP



Heavy Duty, Pre-mixed Coolant 1000L ZFGCC36086HP





Technical specifications and information

For use in all Diesel, Petrol, LPG, Natural Gas and Biodiesel engines

Safe for use with silicon seals and gaskets Dangerous Goods Class - NONE Hazchem Code - NONE Poison Schedule No. - NONE

EPA Spill Reporting - NONE

Biodegradable - YES

Propylene Glycol is generally recognised as safe by the US Food and Drug Administration.

Propylene Glycol is commonly used in medicines, cosmetics and food products.

Meets or exceeds all fully formulated heavy-duty specifications including:

TMC RP-330 (PG) - ASTM D-6210 (EG & PG) - ASTM D-3306 (EG & PG) - CID-A-A52624 - Waukesha® 4-1974D - Cummins® SB 3666132 - Cummins® CES 14603 - Caterpillar® - Detroit Diesel® 7SE298 - John Deere® 8650-5 - Case New Holland® - Navistar® CEMS B-1 - Freightliner® 48-22880 - Volvo® - PACCAR® - MACK® 014617004 - EMD M.I. 1784E - Komatsu® - MAN® 324 SNF - DAF® Standard MAT 74002 - IVECO®

DO NOT ADD WATER.

HIGHWAY PLUS Engine Coolant is a heavy duty extended life coolant that can also be used in standard maintenance programs. For standard maintenance, simply use HIGHWAY PLUS Engine Coolant and change standard, non-chemical coolant filters at normal oil change intervals. Engine Coolant Extender (ZFGCC36091) every 500,000 kilometres or 6,000 hours or as needed.

EXTENDED LIFE PROGRAM:

Topping Up

The engine cooling system can be topped up at any time with HIGHWAY PLUS Coolant.

Maintenance

After 500,000 kilometres or 6,000 hours check coolant quality using test strips (ZFGCC36089). Replenish the system with an addition of Extender liquid (ZFGCC36091) as needed and install a new non-chemical ESI Filter. To guard against dilution caused by water-only top ups, use test strips (ZFGCC36089) to monitor additive levels at least twice a year.

Benefits

- Low maintenance
- Excellent liner pitting protection
- Improves water pump life
- Compatible with all conventional antifreezes
- For all diesel, petrol, LPG, natural gas and biodiesel engines
- Meets North American, European and Asian specifications





Visit highwayplus.com.au to find your closest Dealer!

